

Framework of Continual Commissioning to Produce and Maintain Energy-efficient Buildings

- *definition and examples* -



Nobuo Nakahara

*Prof. Emeritus, Nagoya University:
Chairman, Building Services Commissioning
Association*

NESTEC

Contents

- **Promoting commissioning activities in Japan**
- **International view of HVAC commissioning**
- **Definition of commissioning process**
- **Defining performance goal-OPR, Key to Cx**
- **Simulation for OPR, design Cx and BOFD**
- **Discussion on Continual Commissioning (CC), concept and its new definition for LCCx**
- **Framework of CC and on-going PDCA**
- **Role of BOFD and BEMS (BACS), and BACS Cx.**
- **Principle of Environmental Circle**
- **Topics on GWG issue**

Contents

- **Promoting commissioning activities in Japan**
- **International view of HVAC commissioning**

Definition of commissioning process

Defining performance goal-OPR, Key to Cx

Simulation for OPR, design Cx and BOFD

Discussion on Continual Commissioning, concept and its new definition for LCCx

Framework of CC and on-going PDCA

Role of BOFD and BEMS

Principle of Environmental Circle

Topics on GWG issue

Cx Process Application in Japan and Role of BSCA

2000 Yamatake ERC
PICx

2003 TEPCO T Bldg.
PICx

2005~07 Nisseki
Hospital PICx

2005~2009 Chuden
Atsuta Bldg. RtrCx

2006~09 KEPCO DHC
Nakanoshima RtrCx

1989~2003 Harumi Toriton, Icx~CCx

SHASE BEMS / Commissioning
Committees

1995 ~

Bilding Commission-
ning Association
(BSCA)

2004 ~

CxPE, CA Qualification, Tool Development

Author's Experience as CA on HVAC

- **Harumi DHC, Initial Cx, for System selection**

- Total floor area: **670,000m²**

- Land area: **8ha**

- **From Program phase to Post-acceptance phase**



- **Y Office/Laboratory, Initial (partial) Cx.**

- Approx. **1,700m²**

- **After Construction phase to Operation phase**



- **A Office Building, (full for retrofit stage) RetroCx.**

- Approx. **9,400m²**

- **From Pre-design phase but After FDD to Operation phase**




- **N Hospital Facility, Initial (partial) Cx.**

- Approx. **82,000m²** and Annexes

- **After Schematic design step to Elaboration phase**




International Collaboration on Commissioning





Contents

- Promoting commissioning activities in Japan**
- International view of HVAC commissioning**
- **Definition of commissioning process**
 - Defining performance goal-OPR, Key to Cx**
 - Simulation for OPR, design Cx and BOFD**
 - Discussion on Continual Commissioning, concept and its new definition for LCCx**
 - Framework of CC and on-going PDCA**
 - Role of BOFD and BEMS**
 - Principle of Environmental Circle**
 - Topics on GWG issue**




* 'Life-cycle and 'Continuous' Commissioning do not always mean the continuous payment of commissioning fee to CA, but means that the building owners manage commissioning process strategically and execute commissioning contracting with CA when necessary to preserve optimal performance of the building systems after initial and / or retro-commissioning process. The style and timing of the continuous commissioning working with maintenance personnels and CA depends upon building owners' engineering stance and capability.





Commissioning Process for New Construction



Contents

- Promoting commissioning activities in Japan**
- International view of HVAC commissioning**
- Definition of commissioning process**
 - **Defining performance goal-OPR, Key to Cx**
 - **Simulation for OPR, design Cx and BOFD**
- Discussion on Continual Commissioning, concept and its new definition for LCCx**
- Framework of CC and on-going PDCA**
- Role of BOFD and BEMS**
- Principle of Environmental Circle**
- Topics on GWG issue**

Why HVAC Simulations as Cx?

- **Pre-design Phase**

- **To establish Project Plan and/or OPR for owner's decision-making**

- **Design Phase**


- **Degraded quality of Design Documents, due to**
 - less time
 - less fee
 - less skill, less training
 - **Electronic standard documents easily sum up enormous volume of apparently beautiful docs**
 - **Prevailed distributed packaged system**
 - **Order BACS design outside without sufficient spec. with narratives and flowcharts.**

Why Simulation and Design Cx? **cont.**

- **Design Phase** cont.
 - **Calculation / Simulation Tools developed too further for designers to handle in short worktime.**
 - **And yet, design professionals are erroneously too much expected to do perfect work even with insufficient fee due to excessive competition.**
 - **Building owners should recognize they must anyhow pay for a good job**
 - **Commissioning process during design phase should make sure of successful achievement, and that owners hire well qualified commissioning authority from the third party.**

Energy Plant Menu of TES_ECO

System Structuring Figure



Energy System Options

NESTEC

	System feature	Combination
A0	Non-Storage Centrifugal	INV-driven Centrifugal Ref.(695RT × 4) +Boiler(5t/h × 2)
A2	Thermal Storage Centrifugal + HRHP	Centrifugal (920RT × 2)+HRHP(527/664kW) +Boiler(5t/h × 2)
B2	Thermal Storage w/CGS600kW Centrifugal + HRHP	CGS(600kW) × 2+ExAR(210RT) +Centrifugal(650RT × 2)+HRHP(527/664kW) +Boiler(4t/h × 3)
C2	Thermal Storage w/CGS300kW Centrifugal + HRHP	CGS(300kW) × 2+ExAR(100RT) +Centrifugal (700RT × 2)+HRHP(527/664kW) +Boiler(4t/h × 3)
E1	Thermal Storage E/G=2/1 Complex w/CGS600	CGS(600kW) × 2+ExAR(210RT) +Centrifugal (920RT)+HRHP(527/664kW) +AR(300RT)+Boiler(4t/h × 3)
E2	Thermal Storage E/G=1/1 Complex w/CGS600	CGS(600kW) × 2台+ExAR(210RT) +HRHP(527/664kW) +AR(630RT)+Boiler(5t/h × 3)
F	Non-Storage w/CGS600 AR E/G=0/100	CGS(600kW) × 2+ExAR(210RT) +AR(630RT × 4)+Boiler(5t/h × 5)

Note: HRHP: Heat Recovery Heat Pump, water source



CGS: Co-generation system w/Exhaust gas

ExAR: Exhausted heat driven Absorption machine

NESTEC

Annual primary energy

Annual CO2



Contents

- Promoting commissioning activities in Japan**
- International view of HVAC commissioning**
- Definition of commissioning process**
- Defining performance goal-OPR, Key to Cx**
- Simulation for OPR, design Cx and BOFD**
- **Discussion on Continuous Commissioning, concept and its new definition for LCCx**
- **Framework of CC and on-going PDCA**
- Role of BOFD and BEMS**
- Principle of Environmental Circle**
- Topics on GWG issue**

Continuous Commissioning Process

(ASHRAE 0-2005)

- **Continuous Commissioning Process: A continuation of the Commissioning Process well into the Occupancy and Operations Phase to verify that a project continues to meet current and evolving Owner's Project Requirements. Continuous Commissioning Process activities are on-going for the life of the facility**

On-Going Commissioning Process

(ASHRAE 0-2005)

- **On-Going Commissioning Process:** A continuation of the Commissioning Process well into the Occupancy and Operations Phase to verify that a project continues to meet current and evolving Owner's Project Requirements. **On-Going Commissioning Process activities occur throughout the life of the facility: some of these will be close to continuous in implementation, and others will be either scheduled or un-scheduled (as needed)**

Re-Commissioning

(ASHRAE 0-2005)

- **Re-Commissioning: An application of the Commissioning Process requirements to a project that has been delivered using the Commissioning Process. This may be a scheduled re-commissioning developed as part of an On-Going Commissioning Process, or it may be triggered by use change, operations problems, or other needs**

Continual (or continuous) Commissioning - new definition -

- **Continual (or continuous) commissioning (Cx) consists of on-going Cx carried out by O&M staff and re-Cx by commissioning professionals outside the O&M organization.**
- **The performance goal, or the kind of OPR, for a new cycle of on-going Cx is given in the report of foregoing commissioning process, i.e., either initial-Cx, retro-Cx or re-Cx process.**
- **However, the term 'continual' is just tentatively used in order not to be mistaken for the conventional meaning.**

Continuous Commissioning for Existing Buildings

Operation and Maintenance Stage

(Occupancy & Operation Phase)

Post-Acceptance Step

Post-Post-Acceptance Step

Renewal Process

Follow Initial Cx Process

Pre

Program Phase
(Pre-Design Phase)

Design Phase

Program Step

Planning Step

Preliminary Design Step

After Initial Cx.,
Retro-Cx

On-Going Cx by O&M

CA

Re-Cx by CA

Owner's Decision
for Renewal

CA

Des.

RFP_Des

RFP_CA

OPR


Cx Spec.

Detailed FDD


Cx Plan

NESTEC


O&M' s Organization for Building Services Systems




Relation among Commission Types and Structure of Continuous Cx



On-going Commissioning Process Phases



Life-cycle Commissioning



Contents

- Promoting commissioning activities in Japan**
- International view of HVAC commissioning**
- Definition of commissioning process**
- Defining performance goal-OPR, Key to Cx**
- Simulation for OPR, design Cx and BOFD**
- Discussion on Continuous Commissioning, concept and its new definition for LCCx**
- Framework of CC and on-going PDCA**
- **Role of BOFD and BEMS (BACS), and BACS Cx**
- Principle of Environmental Circle**
- Topics on GWG issue**

BOFDD

BO

**Building
Optimize**

**Diagnose
Bldg.& Systems**

**Dissatisfied
Energy/Environment**

**Performance Function
and Constraints**

OC

Optimization

Optimal Control

In-optimal

Paramater prediction


FD

**Fault
Recovery**


Fault Diagnosis


Fault Detection

NESTEC



Composition of BEMS






Contents

- Promoting commissioning activities in Japan**
- International view of HVAC commissioning**
- Definition of commissioning process**
- Defining performance goal-OPR, Key to Cx**
- Simulation for OPR, design Cx and BOFD**
- Discussion on Continuous Commissioning, concept and its new definition for LCCx**
- Framework of CC and on-going PDCA**
- Role of BOFD and BEMS**
- **Principle of Environmental Circle**
- **Topics on GWG issue**


Principle of Environmental Circle

NESTEC




Principle of Environmental Circle

NESTEC



World CO₂ Exhaustion

2009.12.1 Matsuda




N. Matsuda

NESTEC

World CO₂ Exhaustion

2009.12.1 Matsuda



N. Matsuda

NESTEC

Conclusions

- **Continuous Cx in lifecycle view was introduced together with Cx activity in Japan and international viewpoint.**
- **HVAC simulation tools shall be used both at the initial Cx at pre-design phase and design phase for OPR and design review, and during the continual Cx for BOFD and optimal operation.**
- **On-going realization of building energy efficiency cannot be achieved without involving O&M' s Cx activity.**
- **Continuous, or continual, Cx is newly defined as the combination of on-going Cx by O&M and re-Cx by Cx professionals.**

Conclusions - continued

- The new definition will give O&M staff a strong motivation for their jobs, while they should be fairly paid for their contribution. To energy and cost saving.
- Continual Cx, whether it follows the initial Cx or not, is most desirable to achieve the global goal for energy conservation.
- BEMS, or BACS, shall be well designed and commissioned in order to fully use as the continual Cx tool together with simulations.
- Principle of Environmental Circle, together with global warming gas issue, was discussed.

**Thank you
for your kind attention!**

See you at the next meeting.

